

TRANS-7635

TYPICAL PROPERTIES

COMPOSITION:	Proprietary blend with hydrophobic silica
TYPE:	Nonionic
VISCOSITY (RVT #3 @ 50 RPM)	200-1000 cPs
SPECIFIC GRAVITY	0.90-0.93
APPEARANCE	OPAQUE YELLOW LIQUID
FLASH POINT:	> 450 ° F
PACKAGING:	55 gal drums @ 390# net 275 gal totes @ 2000# net
F.D.A. INFORMATION:	Approved under 21CFR 175.105, 175.300, 176.210, 176.180, 176.170

LIMITED WARRANTY – PLEASE READ CAREFULLY

For any given application, it is the responsibility of the end-user to assess the product for suitability, performance, and safety. Applied Material Solutions' sole warranty is that the product, as supplied at the time of shipment, will meet the specifications described on the Certificate of Analysis. All other warranties, either express or implied, are disclaimed by Applied Material Solutions, including the warranties of merchantability and of fitness for use. Applied Material Solutions' sole liability is limited to the refund of the purchase price or replacement of any product shown to be other than as warranted. Applied Material Solutions disclaims any liability for any incidental or consequential damages resulting from the use of this product.

© 2016 Applied Material Solutions, Inc. All rights reserved.