

**PRODUCT DATA SHEET**

**TRANS-7665 C**

**TYPICAL PROPERTIES (Tentative)**

COMPOSITION:	Water Based Defoamer
TYPE:	Fatty Alcohol Blend
APPEARANCE:	Off white / cream liquid
SPECIFIC GRAVITY:	Approx. 0.95
VISCOSITY @100 F:	400-1000 cps
SOLUBILITY IN WATER:	Emulsifyable
pH:	Neutral
FLASH POINT:	>360 ° F
PACKAGING:	55 gallon steel drums @ 410# net 275 gallon totes @ 2100# net Bulk tanker @ 40,000# net
F.D.A. INFORMATION:	Approved under 21CFR 176.210, 176.200, 175.105, 176.180, 176.170

**LIMITED WARRANTY – PLEASE READ CAREFULLY**

For any given application, it is the responsibility of the end-user to assess the antifoam for suitability, performance, and safety. Applied Material Solutions' sole warranty is that the antifoam, as supplied at the time of shipment, will meet the specifications described on the Certificate of Analysis. All other warranties, either express or implied, are disclaimed by Applied Material Solutions, including the warranties of merchantability and of fitness for use. Applied Material Solutions' sole liability is limited to the refund of the purchase price or replacement of any antifoam shown to be other than as warranted. Applied Material Solutions disclaims any liability for any incidental or consequential damages resulting from the use of this product.

© 2016 Applied Material Solutions, Inc. All rights reserved.