

DEFOAMER AE-10-TG

TYPICAL PROPERTIES

COMPOSITION:	Aqueous emulsion of silicone antifoam
TYPE:	Nonionic
APPEARANCE:	Opaque white emulsion
SPECIFIC GRAVITY:	Approx. 0.98 to 1.02
VISCOSITY @ 25° C:	1000 - 2000 cP
SOLUBILITY IN WATER:	Emulsifiable
FLASH POINT:	None to boiling
PACKAGING:	55 gallon plastic drums @ 450# net 275 gallon totes @ 2250# net
F.D.A. INFORMATION:	Approved under 21CFR177.1200 176.200, 176.210, 175.105, 175.170 and 176.180

LIMITED WARRANTY – PLEASE READ CAREFULLY

For any given application, it is the responsibility of the end-user to assess the antifoam for suitability, performance, and safety. Applied Material Solutions' sole warranty is that the antifoam, as supplied at the time of shipment, will meet the specifications described on the Certificate of Analysis. All other warranties, either express or implied, are disclaimed by Applied Material Solutions, including the warranties of merchantability and of fitness for use. Applied Material Solutions' sole liability is limited to the refund of the purchase price or replacement of any antifoam shown to be other than as warranted. Applied Material Solutions disclaims any liability for any incidental or consequential damages resulting from the use of this product.

© 2016 Applied Material Solutions, Inc. All rights reserved.

Applied Material Solutions, Inc., 1001 E. Centralia Street, Elkhorn, WI 53121
Phone: 262 / 723-6595 Fax: 262 / 723-3830 www.appliedmaterialsolutions.com